




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61M 5/28	A1	(11) International Publication Number: WO 00/69494
		(43) International Publication Date: 23 November 2000 (23.11.00)
<p>(21) International Application Number: PCT/GB00/01811</p> <p>(22) International Filing Date: 11 May 2000 (11.05.00)</p> <p>(30) Priority Data: 9910865.6 12 May 1999 (12.05.99) GB</p> <p>(71) Applicant (for all designated States except US): OWEN MUMFORD LIMITED [GB/GB]; Brook Hill, Woodstock, Oxford OX20 1TU (GB).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): MARSHALL, Jeremy [GB/GB]; 16 Cranham Street, Jericho, Oxford OX2 6DD (GB).</p> <p>(74) Agents: LAINE, Simon, James et al.; Wynne-Jones, Laine & James, 22 Rodney Road, Cheltenham, Gloucestershire GL50 1JJ (GB).</p>		<p>(81) Designated States: JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published <i>With international search report.</i></p>

(54) Title: IMPROVEMENTS RELATING TO MEDICAL SYRINGES



(57) Abstract

A syringe (1) contains a liquid medical substance which has to be mixed with another substance before use. This is done by interconnecting the syringe (1) and a capsule containing the other substance by a transfer device (2) which screws into a socket (4) in the piston-seal (3) of the syringe (1) and penetrates through into the liquid. The device (2) extends slidably but non-rotatably through a screw cap (8) which fits to the rear end of a housing (13) for the syringe (1). As the cap (8) screws on, so does the transfer device (2) screw into the piston-seal (3). The relationship between the screw threads is such that, on removing the screw cap (8), the transfer device (2) disengages from the piston-seal (3) first, so that the latter cannot be inadvertently removed from the syringe.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Improvements relating to Medical Syringes

This invention relates to medical syringes. It is concerned with those where a liquid part of a medical substance is initially kept in a syringe while another part, which may be in liquid or powder form, is in a separate capsule. A transfer device couples the syringe and capsule, and in a preliminary operation the liquid in the syringe is conveyed through its piston-seal to the capsule, where it mixes with the contents, and then back in ready-to-use mixed form to the syringe. The transfer device is decoupled, and a piston rod can then be fitted to the piston seal.

Various arrangements are described in WO 00/13723. However, there is a risk, at the end of the transfer process and when decoupling the transfer device from the syringe, of pulling out the piston seal, and it is the aim of this invention to reduce or possibly eliminate that risk.

According to the present invention there is provided a syringe assembly comprising a syringe with a first liquid medical substance and a transfer device connectable thereto for preparatory mixing of said first substance with a second medical substance in a capsule connectable elsewhere to the transfer device, the syringe having a piston-seal with a screw-threaded socket facing rearwardly to the open end of the syringe, and the transfer device having a needle projecting from its leading end which screws into said recess while the needle penetrates through the piston-seal

into the first substance, wherein a cap is slidable axially up to a forward limit but is non-rotatable with respect to the transfer device which extends co-axially through it, and wherein the cap has screw-threaded engagement with the rear
5 end of the syringe, the arrangement being such that, when the transfer device is offered up to the syringe and the cap at its forward limit is screwed thereto, the transfer device, rotating with the cap, screws into the piston-seal and completes its attachment thereto before the completion
10 of the cap and syringe attachment, and such that the removal of the transfer device is by unscrewing the cap, which frees the transfer device from its engagement with the screw-threaded socket before the cap is freed from the syringe.

Generally, the syringe will have a capsule within a
15 housing with which it is effectively integral, and it is the housing which will have the screw thread for engagement by the cap. In that case, the cap may penetrate into the rear end of the housing and, when screwed fully home, engage the rear end of the capsule to clamp that firmly within the
20 housing.

The pitch of the screw threads may be such that both the cap and the transfer device move forward together in unison. But the axial length of the thread in the socket will then be shorter than the axial length of the cap
25 thread. Alternatively, the socket may have a thread of relatively coarse pitch compared with that of the cap, so that the transfer device advances ahead of the cap until it is fully home in the piston-seal socket. The cap continues

to be screwed on, and "catches up" the transfer device.

For a better understanding of the invention, one embodiment will now be described, by way of example, with reference to the accompanying drawing in which the single figure is an exploded view, partially in axial section, of
5 a transfer device and syringe.

A syringe capsule 1 and a transfer device 2 are substantially as described in WO 00/13723. The capsule 1 contains a liquid medical substance confined by a piston-seal 3 with a central socket 4 in its exposed rear side into
10 which screws the threaded leading end portion or nose 5 of the transfer device. This causes a needle 6 projecting from the nose to penetrate through the piston-seal 3 into the liquid. The needle 6 is hollow and communicates with a
15 transfer canal within the device 2. A second capsule (not shown) with another medical substance to be mixed with the liquid will be fitted to the other end of the transfer device.

At the end of the procedure for preparing the contents
20 of the syringe, the needle 6 has to be withdrawn from the piston-seal 3, the transfer device 2 being replaced by a piston rod to eject the dose. It has been found that there is a danger that, instead of a careful unscrewing action, the syringe and the transfer device can be inadvertently
25 pulled apart before the threads are disengaged, and this plucks the piston-seal 3 out of the syringe, with disastrous results. There is also a risk of retracting the piston-seal too far towards the end of the transfer process, when the

mixed dose is being pulled back into the syringe from the capsule at the other end of the transfer device.

To prevent this, the stem 7 of the transfer device 2 passes through a screw cap 8. It can slide longitudinally with respect to the cap but being of non-circular section, it cannot rotate. An externally screw-threaded portion 9 is forward of an enlarged disc-like head 10, and a plain cylindrical section 11 continues beyond the screw thread. The stem 7 has an annular enlargement 12 immediately behind the nose 5 which is an easy fit into the syringe capsule and which acts as a stop limiting the forward movement of the cap 8 relative to the transfer device.

The capsule 1 locates in a tubular housing 13, its forward end seating in an externally screw threaded neck 14 which will receive a needle assembly (not shown). Conveniently, the housing is transparent, and is marked with a scale to indicate the dose in the capsule 1. At its rear, open end, it is provided with a collar 15 internally screw threaded to receive the cap 8. Externally the collar reduces at a forward facing shoulder 16, and over this lesser diameter portion a casing 17, indicated in broken lines, can snap-fit.

When the coupling element 2 is offered up, the needle 6 enters the socket 4 of the piston-seal 3, which is near the rear end of the filled syringe. The cap 8 is slid forwards along the stem 7 until it meets the enlargement 12 and is screwed into the collar 15. As this happens, so will the nose 5 engage the socket 4 and screw into that.


The screw threaded portion 9 is considerably longer than the portion 5, which ensures that the latter is fully home in the piston-seal 3 before the head 10 meets the rear end face of the collar 15. Over the last few turns of the cap 8, the piston-seal 3 will rotate and advance a short distance, and as the cap seats so the end of the portion 11 comes to bear firmly on the rear end of the syringe capsule 1 and clamp it in position in the housing 13. The small forward movement of the piston-seal 3 causes some of the liquid in the capsule 1, into which the hollow needle 6 has now penetrated, to flow into the canal through the transfer device 2 and possibly reach the capsule at the other end. The rest of the liquid follows during the transfer and mixing process. With the cap 8 in place, there is no chance of the piston-seal 3 escaping.

When the time comes to disengage the transfer device 2, the cap 8 has to be unscrewed. This action also unscrews the nose 5 from the piston-seal 3, and again because of the relative lengths of the screw threaded portions, the piston-seal 3 is disengaged before the cap 8 is clear of the collar 15. Therefore, when the transfer device 2 is pulled clear, the piston-seal 3 will be left safely behind in the syringe 1.

Claims

1. A syringe assembly comprising a syringe with a first liquid medical substance and a transfer device connectable thereto for preparatory mixing of said first substance with
5 a second medical substance in a capsule connectable elsewhere to the transfer device, the syringe having a piston-seal with a screw-threaded socket facing rearwardly to the open end of the syringe, and the transfer device having a needle projecting from its leading end which screw into said
10 recess while the needle penetrates through the piston-seal into the first substance, wherein a cap is slidable axially up to a forward limit but is non-rotatable with respect to the transfer device which extends co-axially through it, and wherein the cap has screw-threaded engagement with the rear
15 end of the syringe, the arrangement being such that, when the transfer device is offered up to the syringe and the cap at its forward limit is screwed thereto, the transfer device, rotating with the cap, screws into the piston-seal and completes its attachment thereto before the completion
20 of the cap and syringe attachment, and such that the removal of the transfer device is by unscrewing the cap, which frees the transfer device from its engagement with the screw-threaded socket before the cap is freed from the syringe.
2. A syringe assembly as claimed in Claim 1, wherein the
25 syringe has a capsule within a housing with which it is effectively integral, and it is the housing which has the screw thread for engagement by the cap.

3. A syringe assembly as claimed in Claim 2, wherein the cap penetrates into the rear end of the housing and, when screwed fully home, engages the rear end of the capsule to clamp that firmly within the housing.



INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 00/01811

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61M5/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61M A61J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, A	WO 00 13723 A (MEYER GABRIEL ; OWEN MUMFORD LTD (GB)) 16 March 2000 (2000-03-16) cited in the application the whole document ---	1
A	WO 98 57734 A (FUSION MEDICAL TECHNOLOGIES IN) 23 December 1998 (1998-12-23) abstract; figures 1-5 ---	1
A	US 5 472 022 A (MICHEL PETER ET AL) 5 December 1995 (1995-12-05) abstract; figure 2 ---	1
A	US 4 642 103 A (GETTIG WILLIAM A) 10 February 1987 (1987-02-10) abstract; figures 1-4 ---	1
	--- -/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

30 August 2000

Date of mailing of the international search report

06/09/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Jameson, P

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 00/01811

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>WO 97 07839 A (MDC INVESTMENT HOLDINGS INC) 6 March 1997 (1997-03-06) page 11, line 8 -page 12, line 9; figure 1A page 18, line 31 -page 19, line 25; figure 3 -----</p>	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 00/01811

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 0013723 A	16-03-2000	AU 5639099 A	27-03-2000
WO 9857734 A	23-12-1998	US 5957166 A	28-09-1999
		AU 8258098 A	04-01-1999
		US 5908054 A	01-06-1999
US 5472022 A	05-12-1995	AT 177013 T	15-03-1999
		CA 2175573 A	11-05-1995
		DE 69416851 D	08-04-1999
		DE 69416851 T	04-11-1999
		EP 0726786 A	21-08-1996
		ES 2131711 T	01-08-1999
		GR 3030393 T	30-09-1999
		JP 9510880 T	04-11-1997
		WO 9512425 A	11-05-1995
US 4642103 A	10-02-1987	NONE	
WO 9707839 A	06-03-1997	AU 6858396 A	19-03-1997
		CA 2229940 A	06-03-1997
		CN 1199344 A	18-11-1998
		EP 0902694 A	24-03-1999
		JP 11511358 T	05-10-1999
		US 5788677 A	04-08-1998